

Elan^{IC} Do more. Feel good.

Blatchford

The best thing about ElanIC is that it's waterproof, so I can play with my daughter, paddle in water and not have to worry about it getting wet. ElanIC is the world's lightest and most compact waterproof microprocessor hydraulic ankle, which combines our awardwinning prosthetic technology with the latest induction charging, meaning you can do more each day.

Designed to meet your unique needs as an amputee, ElanIC mimics the natural function of the foot and ankle, adapting hydraulic resistance and providing exceptional energy return to give you stability on slopes, steps and uneven terrain. By enabling you to distribute weight evenly when standing and walking, the result is a smoother, safer, more natural walking experience.



Ramp Brake: On walking downhill, lower plantar flexion resistance allows the foot to fully contact the slope sooner for improved safety and security. At the same time, increased dorsiflexion resistance provides a braking effect stabilising the user for a safer, more controlled descent.

Banic



Ramp Assist/Fast Walk: When walking quickly or up slopes, the plantar flexion resistance increases allowing for more optimal energy storage and return. Combined with a softer dorsiflexion resistance, this aids forward momentum, body position and minimises the effort required for fast or uphill walking



Standing Support: Standing for longer periods is easier with ElanIC. A network of sensors detect the user is stationary, increasing resistance to help improve balance, stability, reduce effort and encourage a more natural posture.



Swing Clearance: During swing phase, the ankle remains in a dorsiflexed position increasing toe clearance on every step and reducing the risk of stumbles or falls.

Scientifically proven* to provide long-term health benefits.

Improved safety

Greater control and safety



5

Increased confidence in walking and negotiating

chance of trips and falls²

18% increase in toe

variable terrain³⁻⁵

clearance¹ reduces the

Greater comfort



Pressure on residual limb is reduced by 60% ⁶

12

Balanced limb loading



Reduced chance of long term limb disease 7,8



Patient satisfaction



Up to 20% reduction in energy costs on slopes⁹

33.4% increase for bilateral patients ¹⁰

*Clinical studies, latest research papers and full references available on our website https://www.blatchford.co.uk/prosthetics/professionals/clinical-evidence/



Do more. Feel Good.

The all-new waterproof ElanIC enables you to do things you love and take care of your long-term health. This hydraulic ankle works hard to give you the support you need while protecting your bones and joints from the additional wear and tear that is common for many users of prosthetic limbs.

Our design approach is led by your unique needs as an amputee. At Blatchford we specialise in understanding the dynamic and adaptive qualities of natural limb movement, so that you have an experience that is as close to a human ankle as possible, leaving you to focus on doing what you love and feeling good.

Peace of Mind

Featuring simple and safe induction charging technology, ElanIC is completely sealed from the elements meaning that it is waterproof, giving you peace of mind around water.

When you're a Mum you never stop. Before I would have to sit down and take my prosthesis off but with ElanIC I can just keep going.

Sian



IP67 Waterproof

- Submersible up to 1m
- ✓ For up to 30 minutes
- Dustproof
- Showerproof and weatherproof

Product Features

- Integrated Bluetooth® •
- Clinician Programming App •
- Microprocessor controlled plantarflexion and dorsiflexion
- Standing support mode increases resistance when stationary to help improve • balance, stability, reduce effort and encourage a more natural posture
- Variable response to speed changes ٠
- Increased plantarflexion resistance allows for more energy storage and return • when walking quickly or up slopes
- Ankle dorsiflexion during the swing phase increases toe clearance and reduces • the risk of trips and falls
- Increased dorsiflexion resistance provides a brake when walking down slopes • for improved safety and stability
- Waterproof IP67 •
- Induction charging •

Sandal Toe Foot Shell •

Technical Specification

Max User Weight	125kg	Heel Height
Activity Level	(2) 3 (4*)	Range of Move
Size Range	22-30 (sizes 25-27 available	Waterproof
	in Narrow and Wide)	Charging Type
Component Weight without footshell	1kg	Battery Life
Component Weight with footshell	1.24kg	
Build Height	Sizes 22-26: 172mm	Sondol Too Fo
	Sizes 27-30: 177mm	Sanual foe Foe
		Warranty

10mm 6° PF / 3° DF ement Rated IP 67 Induction up to 48 hours^ 5.5 hours ot Shell Yes 36 Months

Ordering Information

Product Code	Size	Side	Width*	Spring Set	Sandal Toe
ELANIC	25	L	N	3	S

*Narrow (N) and Wide (W) available for sizes 25-27 only. For dark tone add suffix D.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG Inc., and any use of such marks by Blatchford is under License. Avoid exposing the device to abrasive or corrosive environments, such as those containing sand, acids, salt, chlorinated, or chemically treated water. *Maximum user weight 100 kg and always use one higher spring rate category than shown in Spring selection table. ^Dependant on activity levels and battery age.

Elan^{ic}



References

- 1. Johnson L, De Asha AR, Munjal R, Kulkarni J, Buckley JG. Toe clearance when walking in people with unilateral transtibial amputation: Effects of passive hydraulic ankle. Journal of Rehabilitation Research and Development (JRRD) 2014;51 (3), 429-438
- Riveras M, Ravera E, Ewins D, Shaheen AF, Catalfamo-Formento P. Minimum toe clearance and tripping probability in people with unilateral transtibial amputation walking on ramps with different prosthetic designs. Gait & Posture. 2020;81:41-8.
- McGrath M, Laszczak P, Zahedi S, Moser D. The influence of a microprocessor-controlled hydraulic ankle on the kinetic symmetry of trans-tibial amputees during ramp walking: a case series. J Rehabil Assist Technol Eng. 2018;5:2055668318790650.
- Bai X, Ewins D, Crocombe AD, Xu W. A biomechanical assessment of hydraulic ankle-foot devices with and without micro-processor control during slope ambulation in trans-femoral amputees. PLOS ONE. 2018 Oct 5;13(10):e0205093.
- Struchkov V, Buckley JG. Biomechanics of ramp descent in unilateral trans-tibial amputees: Comparison of a microprocessor controlled foot with conventional anklefoot mechanisms. Clin Biomech. 2016;32:164–170.
- S. Portnoy, A. Kristal, A. Gefen, I. Siev-Ner. Outdoor dynamic subject-specific evaluation of internal stresses in the residual limb: Hydraulic energy-stored prosthetic foot compared to conventional energy-stored prosthetic feet. Gait and Posture 2012: 35 (1), 121-5
- McGrath M, Laszczak P, Zahedi S, Moser D. The influence of a microprocessor-controlled hydraulic ankle on the kinetic symmetry of trans-tibial amputees during ramp walking: a case series. J Rehabil Assist Technol Eng. 2018;5:2055668318790650.
- McGrath M, Davies KC, Laszczak P, Rek B, McCarthy J, Zahedi S, Moser D. The influence of hydraulic ankles and microprocessor-control on the biomechanics of trans-tibial amputees during quiet standing on a 5° slope. Can Prosthet Orthot J. 2019;2(2).
- Askew GN, McFarlane LA, Minetti AE, Buckley JG. Energy cost of ambulation in trans-tibial amputees using a dynamic-response foot with hydraulic versus rigid 'ankle': insights from body centre of mass dynamics. J NeuroEngineering Rehabil. 2019;16(1):39.
- 10. Sedki I, Moore R. Patient evaluation of the Echelon foot using the Seattle Prosthesis Evaluation Questionnaire, Prosthetics and Orthotics International 2013: 37(3), 250-254

An annual visual inspection is recommended. Check for visual defects that may affect proper function. Maintenance must be carried out by competent personnel. Before carrying out any new activities of daily living, please check with your clinician whether specific training is required.

+44 (0) 1256 316600 | customer.service@blatchford.co.uk Blatchford Products Limited, Unit D Antura, Kingsland Business Park, Basingstoke, RG24 8PZ, United Kingdom.

@blatchfordgrp | blatchford.co.uk

507051192 lss1 07/20. Information correct at time of print.

